

RStudio IDE Commands

Table of contents

The following table enumerates all of the commands currently supported by RStudio. These command IDs can be used in RStudio API calls such as `rstudioapi::executeCommand`.

Id	Description
<code>activateBackgroundJobs</code>	Show Background Jobs
<code>activateBuild</code>	Show Build
<code>activateCompilePDF</code>	Show Compile PDF
<code>activateConnections</code>	Show Connections
<code>activateConsole</code>	Move Focus to Console
<code>activateConsolePane</code>	Move Focus to Console Panel
<code>activateData</code>	Show Data
<code>activateDeployContent</code>	Show Deploy Content
<code>activateEnvironment</code>	Show Environment
<code>activateFiles</code>	Show Files
<code>activateFindInFiles</code>	Show Find in Files
<code>activateHelp</code>	Move Focus to Help
<code>activateHistory</code>	Show History
<code>activateMarkers</code>	Show Markers
<code>activatePackages</code>	Show Packages
<code>activatePlots</code>	Show Plots
<code>activatePresentation</code>	Show Presentation
<code>activatePresentation2</code>	Show Presentation
<code>activateRMarkdown</code>	Show R Markdown
<code>activateSource</code>	Move Focus to Source
<code>activateSourceCpp</code>	Show Source Cpp
<code>activateSQLResults</code>	Show SQL Results
<code>activateTerminal</code>	Move Focus to Terminal
<code>activateTutorial</code>	Show Tutorial

Id	Description
activateVcs	Show Vcs
activateViewer	Show Viewer
activateWorkbenchJobs	Show Workbench Jobs
addCursorAbove	Add Cursor Above Current Cursor
addCursorBelow	Add Cursor Below Current Cursor
authoringRPresentationsHelp	Guide to using R Markdown
browseAddins	Browse addins
browseCheatSheets	Browse available cheat sheets in your web browser
buildAll	Install the package and restart R
buildBinaryPackage	Build a binary package
buildFull	Clean, install the package, and restart R
buildIncremental	Install the package and restart R
buildSourcePackage	Build a source package
buildToolsProjectSetup	Configure build tools
checkForUpdates	Check for Updates
checkPackage	R CMD check
checkSpelling	Check spelling in document
cleanAll	Clean all
clearBackgroundJobs	Clean up all completed background jobs
clearBuild	Clear build
clearCommandPaletteMru	Clear Recently Executed Command List
clearHelpHistory	Clear history
clearHistory	Clear all history entries
clearKnitrCache	Clear the knitr cache for the current document
clearPlots	Clear all Plots
clearPrerenderedOutput	Clear the prerendered output for the current document
clearPresentationCache	Clear knitr cache for this presentation
clearRecentFiles	Clear List
clearRecentProjects	Clear Project List
clearTerminalScrollbackBuffer	Clear terminal
clearUserPrefs	Clear User Prefs
clearWorkspace	Clear objects from the workspace
closeAllSourceDocs	Close All
closeAllTerminals	Close All Terminals
closeOtherSourceDocs	Close All Except Current
closeProject	Close the currently open project
closeSourceDoc	Close
closeTerminal	Close current terminal session
codeCompletion	Show code completions at the current cursor location
commentUncomment	Comment or uncomment the current line/selection
compileNotebook	Compile a report from the current R script

Id	Description
compilePDF	Compile a PDF from the current LaTeX or Sweave document
consoleClear	Clear console
copyDummy	Copy
copyFile	Copy selected file or folder
copyFileTo	Copy selected file or folder to another folder
copyLinesDown	Copy Lines Down
copyPlotToClipboard	Copy the current plot to the clipboard
copySourceDocPath	Copy current document path
crashDesktopApplication	Crash RStudio Desktop (DANGER)
cutDummy	Cut
debugBreakpoint	Set or remove a breakpoint on the current line of code
debugClearBreakpoints	Remove all the breakpoints in the current project
debugContinue	Continue execution until the next breakpoint is encountered
debugDumpContents	Dump Editor Contents...
debugFinish	Execute the remainder of the current function or loop
debugHelp	Guide to debugging features
debugImportDump	Import Editor Contents...
debugStep	Execute the next line of code
debugStepInto	Step into the current function call
debugStop	Exit debug mode
deleteFiles	Delete selected files or folders
devtoolsLoadAll	Execute devtools::load_all
diagnosticsReport	Write Diagnostics Report
disconnectConnection	Disconnect from a connection
editCodeSnippets	Edit code snippets
editLinesFromStart	Create a new cursor at start of each line in selection
editRmdFormatOptions	Edit the R Markdown format options for the current file
editUserPrefs	Edit User Prefs File
enableProsemirrorDevTools	Enable Prosemirror DevTools
errorsBreak	Break when any unhandled error occurs
errorsMessage	Print the error message when an unhandled error occurs
errorsTraceback	Show the error inspector when an unhandled error occurs
executeAllCode	Run all of the code in the source file
executeCode	Run the current line or selection
executeCodeWithoutMovingCursor	Run the current line or selection without moving the cursor
executeCurrentChunk	Run the current code chunk
executeCurrentFunction	Run the top-level function definition, if any, that contains the cursor
executeCurrentLine	Execute the line which contains the cursor
executeCurrentParagraph	Execute the current paragraph of code, delimited by blank lines.

Id	Description
executeCurrentSection	Run the code section that contains the cursor
executeCurrentStatement	Execute the entire R statement which contains the cursor.
executeFromCurrentLine	Run from the current line through the end of the source file
executeLastCode	Re-run the previous code region
executeNextChunk	Run the next code chunk
executePreviousChunks	Run all chunks above the current one
executeSetupChunk	Run the initial setup chunk
executeSubsequentChunks	Run all chunks below the current one
executeToCurrentLine	Run from the beginning of the source file up through the current line
expandSelection	Expand selection
expandToLine	Expand Selection to Line
expandToMatching	Expand selection to matching bracket
exportFiles	Export selected files or folders
extractFunction	Turn the current selection into a function
extractLocalVariable	Extract a variable out of the current selection
findFromSelection	Use Selection for Find
findInFiles	Find in Files...
findNext	Find next occurrence
findPrevious	Find previous occurrence
findReplace	Find...
findSelectAll	Find and select all matches
findUsages	Find source locations where this symbol is used
firstTab	First Tab
focusCenterSeparator	Adjust Center Splitter
focusConsoleOutputEnd	Focus Console Output
focusLeftSeparator	Adjust Left Splitter
focusMainToolbar	Focus Main Toolbar
focusNextPane	Focus Next Pane
focusPreviousPane	Focus Previous Pane
focusRightSeparator	Adjust Right Splitter
focusSourceColumnSeparator	Adjust Source Column Splitter
fold	Collapse
foldAll	Collapse All
forceQuitSession	Quit the current R session even if busy
freeUnusedMemory	Free Unused R Memory
goToDefinition	Go to to the definition of the currently selected function
goToFileFunction	Go To File/Function...
goToHelp	Go to help for the currently selected function
goToLine	Go to Line...
goToNextChunk	Go to next chunk

Id	Description
goToNextSection	Go to next section/chunk
goToPrevChunk	Go to previous chunk
goToPrevSection	Go to previous section/chunk
gotoProfileSource	Open sources associated with the selection
goToWorkingDir	View the current working directory
helpBack	Previous topic
helpForward	Next topic
helpHome	Show R Help
helpKeyboardShortcuts	Keyboard Shortcuts Help
helpPopout	Show in new window
helpSearch	Search R Help
helpUsingRStudio	RStudio Docs
hideToolbar	Hide Toolbar
historyDismissContext	Back
historyDismissResults	Done
historyRemoveEntries	Remove the selected history entries
historySendToConsole	Send the selected commands to the R console (Enter)
historySendToSource	Insert the selected commands into the current document (Shift+Enter)
importDatasetFromCsv	From CSV
importDatasetFromCsvUsingBase	From Text (base)...
importDatasetFromCsvUsingReadr	From Text (readr)...
importDatasetFromFile	From Local File...
importDatasetFromSAS	From SAS...
importDatasetFromSAV	From SPSS...
importDatasetFromStata	From Stata...
importDatasetFromURL	From Web URL...
importDatasetFromXLS	From Excel...
insertChunk	Insert a new code chunk
insertChunkBash	Insert a new Bash chunk
insertChunkD3	Insert a new D3 chunk
insertChunkPython	Insert a new Python chunk
insertChunkR	Insert a new R chunk
insertChunkRcpp	Insert a new Rcpp chunk
insertChunkSQL	Insert a new SQL chunk
insertChunkStan	Insert a new Stan chunk
insertRoxygenSkeleton	Insert a roxygen comment for the current function
insertSection	Insert a new code section
insertSnippet	Expand snippet at cursor
installPackage	Install R packages
interruptR	Interrupt R

Id	Description
interruptTerminal	Send Ctrl+C to Current Terminal
joinLines	Join Lines
jumpTo	Jump To...
jumpToMatching	Jump to matching bracket
knitDocument	Knit the current document
knitWithParameters	Knit the document with a set of custom parameters
lastTab	Last Tab
layoutConsoleOnLeft	Console on Left
layoutConsoleOnRight	Console on Right
layoutEndZoom	Show All Panes
layoutZoomBuild	Zoom Build
layoutZoomConnections	Zoom Connections
layoutZoomConsole	Zoom Console
layoutZoomConsolePane	Zoom Console Pane
layoutZoomEnvironment	Zoom Environment
layoutZoomFiles	Zoom Files
layoutZoomHelp	Zoom Help
layoutZoomHistory	Zoom History
layoutZoomLeftColumn	Zoom Left / Center Column
layoutZoomPackages	Zoom Packages
layoutZoomPlots	Zoom Plots
layoutZoomPresentation2	Zoom Presentation
layoutZoomRightColumn	Zoom Right Column
layoutZoomSource	Zoom Source
layoutZoomTutorial	Zoom Tutorial
layoutZoomVcs	Zoom VCS
layoutZoomViewer	Zoom Viewer
loadHistory	Load history from an existing file
loadServerHome	Posit Workbench Home
loadWorkspace	Load workspace
logFocusedElement	Log focused element
macPreferences	Preferences...
markdownHelp	Markdown quick reference
maximizeConsole	Maximize Console
modifyKeyboardShortcuts	Modify keyboard shortcuts
moveFiles	Move selected files or folders
moveLinesDown	Move Lines Down
moveLinesUp	Move Lines Up
moveTabLeft	Move Tab Left
moveTabRight	Move Tab Right
moveTabToFirst	Move Tab to First

Id	Description
moveTabToLast	Move Tab to Last
newCDoc	Create a new C file
newConnection	Create a new connection
newCppDoc	Create a new C++ file
newCssDoc	Create a new CSS file
newD3Doc	Create a new D3 Script
newFolder	Create a new folder
newHeaderDoc	Create a new header file
newHtmlDoc	Create a new HTML file
newJavaScriptDoc	Create a new JavaScript file
newMarkdownDoc	Create a new Markdown document
newProject	Create a project
newPythonDoc	Create a new Python script
newQuartoDoc	Create a new Quarto document
newQuartoPres	Create a new Quarto presentation
newRDocumentationDoc	Create a new Rd documentation file
newRHTMLDoc	Create a new R HTML document
newRMarkdownDoc	Create a new R Markdown document
newRNotebook	Create a new R Markdown notebook
newRPlumberDoc	Create a new Plumber API
newRPresentationDoc	Create a new R presentation
newRShinyApp	Create a new Shiny web application
newSession	Open a new R session
newShellDoc	Create a new shell script
newSourceColumn	Add Source Column
newSourceDoc	Create a new R script
newSqlDoc	Create a new SQL script
newStanDoc	Create a new Stan program
newSweaveDoc	Create a new R Sweave document
newTerminal	Create a new terminal
newTextDoc	Create a new text file
nextPlot	Next plot
nextTab	Next Tab
nextTerminal	Show next terminal
notebookClearAllOutput	Remove all code chunk output in the current file
notebookClearOutput	Clear the output of the current notebook chunk
notebookCollapseAllOutput	Collapse all code chunk output in the current file
notebookExpandAllOutput	Expand all code chunk output in the current file
notebookToggleExpansion	Expand or collapse the output of the current notebook chunk
openDataImportCheatSheet	Import data with readr
openDataTransformationCheatSheet	Data transformation with dplyr

Id	Description
openDataVisualizationCheatSheet	Data visualization with ggplot2
openDataWranglingCheatSheet	Data manipulation with dplyr and tidyr
openDeveloperConsole	Open Developer Console
openHtmlExternal	View the page with the system web browser
openNewTerminalAtEditorLocation	Open New Terminal at File Location
openNewTerminalAtFilePanelLocation	Open New Terminal Here
openPackageDevelopmentCheatSheet	Package development with devtools
openProfile	Opens a profile from a file
openProfileInBrowser	Opens current profile in a web browser
openProject	Open a project
openProjectInNewWindow	Open project in a new R session
openPurrrCheatSheet	List manipulation with purrr
openRMarkdownCheatSheet	R Markdown cheat sheet
openRMarkdownReferenceGuide	R Markdown reference guide
openRoxygenQuickReference	Roxygen quick reference
openRStudioIDECheatSheet	RStudio IDE cheat sheet
openSharedProject	Open a project shared with you
openShinyCheatSheet	Build web applications with Shiny
openSourceDoc	Open an existing file
openSourceDocNewColumn	Open an existing file in a new column
openSparklyrCheatSheet	Interfacing Apache Spark with sparklyr
packratBootstrap	Use packrat with this project
packratBundle	Bundle a Packrat Project
packratCheckStatus	Check the status of the Packrat library
packratClean	Remove unused packages from your packrat library
packratHelp	Help on using packrat with R projects
packratOptions	Configure packrat options for this project
paneLayout	Pane Layout...
pasteDummy	Paste
pasteWithIndentDummy	Paste with Indent
plumberRunInBrowser	Run the Plumber API in the system's default Web browser
plumberRunInPane	Run the Plumber API in an RStudio pane
plumberRunInViewer	Run the Plumber API in an RStudio viewer window
popoutDoc	Show in new window
presentation2Edit	Edit this slide of the presentation
presentation2Home	Go to the first slide
presentation2Next	Go to the next slide
presentation2Present	Present in an external web browser
presentation2PresentFromBeginning	Present from the first slide in an external web browser
presentation2Prev	Go to the previous slide
presentation2Print	Open a browser to print the presentation

Id	Description
presentationEdit	Edit this slide of the presentation
presentationFullscreen	Show presentation in full screen mode
presentationHome	Go to the first slide
presentationNext	Go to the next slide
presentationPrev	Go to the previous slide
presentationSaveAsStandalone	Save the presentation as a standalone web page
presentationViewInBrowser	View the presentation in an external web browser
previewHTML	Show a preview of the current document as HTML
previewJS	Preview the active JavaScript document
previewSql	Preview the active SQL document
previousPlot	Previous plot
previousTab	Previous Tab
previousTerminal	Show previous terminal
printCppCompletions	Print C++ Completions
printHelp	Print topic
printSourceDoc	Print the current file
profileCode	Profile the current line or selection
profileHelp	Guide to profiling features
projectOptions	Edit options for the current project
publishHTML	Publish the current document
quartoRenderDocument	Render the current document
quickAddNext	Find and add next occurrence
quitSession	Quit the current R session
raiseException	Raise Exception
raiseException2	Raise Exception JS
rcppHelp	Help on using Rcpp
redoDummy	Redo
reflowComment	Reflow selected comment lines so they wrap evenly
reformatCode	Reformat the current line/selection
refreshConnection	Refresh data
refreshEnvironment	Refresh the list of objects in the environment
refreshFiles	Refresh file listing
refreshFindInFiles	Refresh Find in Files results
refreshHelp	Refresh topic
refreshHtmlPreview	Refresh the preview
refreshPackages	Refresh Package listing
refreshPlot	Refresh current plot
refreshPresentation	Refresh the presentation
refreshPresentation2	Refresh the presentation preview
refreshWorkspace	Refresh Workspace
reindent	Reindent the current line/selection

Id	Description
reloadPlumberAPI	Reload the Plumber API
reloadShinyApp	Reload the Shiny application
reloadUi	Reload UI
removeConnection	Remove connection from the connection history
removeLine	Remove Line
removePlot	Remove the current plot
renameFile	Rename selected file or folder
renameInScope	Rename symbol in current scope
renameSourceDoc	Rename current document
renameTerminal	Change terminal session name
renvHelp	Learn how to use renv
renvRestore	Restore your project library from renv.lock
renvSnapshot	Snapshot the state of your project library
reopenSourceDocWithEncoding	Reopen the current file with a different encoding
replaceAndFind	Replace and find next occurrence
restartR	Restart R
restartRClearOutput	Restart R session and clear chunk output
restartRRunAllChunks	Restart R session and run all chunks
returnDocToMain	Return to main window
roxygenizePackage	Build package documentation
rsconnectConfigure	Configure the application
rsconnectDeploy	Publish the application or document
rsconnectManageAccounts	Connect or disconnect accounts
rstudioCommunityForum	RStudio Community Forum
rstudioLicense	RStudio License
rstudioSupport	Posit Support
runDocumentFromServerDotR	Run the interactive document
runSelectionAsBackgroundJob	Run the selected code as a background job
runSelectionAsWorkbenchJob	Run the selected code as a Workbench job
saveAllSourceDocs	Save all open documents
saveHistory	Save history into a file
saveHtmlPreviewAs	Save the page to another location
saveHtmlPreviewAsLocalFile	Download the page to a local file
savePlotAsImage	Save the current plot as an image file
savePlotAsPdf	Save the current plot as a PDF file
saveProfileAs	Saves current profile into a file
saveSourceDoc	Save current document
saveSourceDocAs	Save current file to a specific path
saveSourceDocWithEncoding	Save the current file with a different encoding
saveWorkspace	Save workspace as
selectAllDummy	Select All

Id	Description
sendFilenameToTerminal	Send Filename to Terminal
sendTerminalToEditor	Copy current terminal's buffer to a new editor buffer
sendToTerminal	Send the current line or selection to terminal
serveQuartoSite	Run development server for Quarto site
setTerminalToCurrentDirectory	Go to Current Directory
setWorkingDir	Select and change to a new working directory
setWorkingDirToActiveDoc	Change working directory to path of active document
setWorkingDirToFilesPane	Change working directory to location of Files pane
setWorkingDirToProjectDir	Change working directory to project root directory
shareProject	Share this project with others
shinyCompareTest	Compare test results for Shiny application
shinyRecordTest	Record test for Shiny application
shinyRunAllTests	Run tests for Shiny application
shinyRunInBrowser	Run the Shiny application in the system's default Web browser
shinyRunInPane	Run the Shiny application in an RStudio pane
shinyRunInViewer	Run the Shiny application in an RStudio viewer window
showA11yDiagnostics	Show Accessibility Diagnostics
showAboutDialog	About RStudio
showAccessibilityHelp	Accessibility Help...
showAccessibilityOptions	Accessibility Options...
showBuildMenu	Show Build Menu
showCodeMenu	Show Code Menu
showCommandPalette	Show Command Palette
showDebugMenu	Show Debug Menu
showDiagnosticsActiveDocument	Show diagnostics for the active document
showDiagnosticsProject	Show diagnostics for all source files in the current project
showDomElements	Show DOM Elements
showEditMenu	Show Edit Menu
showFileMenu	Show File Menu
showGpuDiagnostics	Show GPU Diagnostics
showHelpMenu	Show Help Menu
showHtmlPreviewLog	Show the compilation log for this document
showLicenseDialog	Manage License...
showLogFiles	Show Log Files
showManipulator	Show the manipulator for this plot
showMemoryUsageReport	Memory Usage Report...
showOptions	Global Options...
showPdfExternal	Show in an external PDF viewer window
showPlotsMenu	Show Plots Menu
showProfileMenu	Show Profile Menu

Id	Description
showRequestLog	Show internal request log
showSessionMenu	Show Session Menu
showSessionServerOptionsDialog	Configure available session servers
showShortcutCommand	Show Keyboard Shortcut Commands
showTerminalInfo	Show info on current terminal
showTerminalOptions	Terminal Options...
showToolbar	Show Toolbar
showToolsMenu	Show Tools Menu
showViewMenu	Show View Menu
showWarningBar	Show warning bar
shrinkSelection	Shrink selection
signOut	Sign out from RStudio
sortWorkbenchJobsRecorded	Sort Workbench jobs by time submitted
sortWorkbenchJobsState	Sort Workbench jobs by current state
sourceActiveDocument	Source the contents of the active document
sourceActiveDocumentWithEcho	Source the contents of the active document (with echo)
sourceAsJob	Run the current R script as a background job
sourceAsWorkbenchJob	Run the current R script on a cluster
sourceFile	Source the contents of an R file
sourceNavigateBack	Go back to the previous source location
sourceNavigateForward	Go forward to the next source location
sparkHelp	Help on using Spark with RStudio
sparkLog	View the log for the Spark connection
sparkUI	View the browser UI for the Spark connection
speakEditorLocation	Speak Text Editor Location
splitIntoLines	Create a new cursor on each line in current selection
startJob	Run a background local job
startProfiler	Start profiling R code
startWorkbenchJob	Run a job on a cluster
stopBuild	Stop the current build
stopProfiler	Stop profiling R code
suspendSession	Suspend R Session
switchToChunkBash	Switch chunk to Bash
switchToChunkPython	Switch chunk to Python
switchToChunkR	Switch chunk to R
switchToChunkRcpp	Switch chunk to Rcpp
switchToChunkSQL	Switch chunk to SQL
switchToChunkStan	Switch chunk to Stan
switchToTab	Switch to Tab...
synctexSearch	Sync PDF view to editor location (Ctrl+Click)
terminateR	Forcibly terminate R session

Id	Description
testPackage	Run tests for package
testShinytestFile	Run test using the shinytest package
testTestthatFile	Run tests using the testthat package
toggleDocumentOutline	Show document outline
toggleEditorTokenInfo	Toggle Editor Token Information
toggleFullScreen	Toggle Full Screen
toggleRainbowFencedDivs	Rainbow Fenced Divs
toggleRainbowParens	Rainbow Parentheses
toggleRmdVisualMode	Switch markdown editing mode
toggleScreenReaderSupport	Screen Reader Support
toggleShowMemoryUsage	Show Current Memory Usage
toggleSoftWrapMode	Soft Wrap Long Lines
toggleTabKeyMovesFocus	Tab Key Always Moves Focus
toggleToolbar	Toggle Toolbar
touchCDoc	Create a blank C file in current directory
touchCppDoc	Create a blank C++ file in current directory
touchCssDoc	Create a blank CSS file in current directory
touchD3Doc	Create a blank D3 script in current directory
touchHeaderDoc	Create a blank header file in current directory
touchHtmlDoc	Create a blank HTML file in current directory
touchJavaScriptDoc	Create a blank JavaScript file in current directory
touchMarkdownDoc	Create a blank Markdown document in current directory
touchPythonDoc	Create a blank Python script in current directory
touchQuartoDoc	Create a blank Quarto document in current directory
touchRHTMLDoc	Create a blank R HTML document in current directory
touchRMarkdownDoc	Create a blank R Markdown document in current directory
touchShellDoc	Create a blank shell script in current directory
touchSourceDoc	Create a blank R script in current directory
touchSqlDoc	Create a new SQL script in current directory
touchStanDoc	Create a blank Stan program in current directory
touchSweaveDoc	Create a blank R Sweave document in current directory
touchTextDoc	Create a blank text file in current directory
tutorialBack	Go back
tutorialForward	Go forward
tutorialHome	Return to home
tutorialPopout	Show in new window
tutorialRefresh	Refresh tutorial
tutorialStop	Stop tutorial
tutorialZoom	View a larger version in a new window
undoDummy	Undo
unfold	Expand

Id	Description
unfoldAll	Expand All
updateCredentials	Update Credentials
updatePackages	Check for package updates
uploadFile	Upload files to server
usingRMarkdownHelp	Guide to using R Markdown
vcsAddFiles	Add the selected files or folders
vcsBlameOnGitHub	Blame view for this file on Github
vcsCleanup	Recursively clean up the working copy (removing locks, etc)
vcsCommit	Commit pending changes
vcsDiff	Diff selected file(s)
vcsFileDiff	Show differences for the file
vcsFileLog	Show log of changes to the file
vcsFileRevert	Revert changes to the file
vcsIgnore	Ignore the selected files or folders
vcsOpen	Open selected file(s)
vcsPull	Pull Branches
vcsPullRebase	Pull with Rebase
vcsPush	Push Branch
vcsRefresh	Refresh listing
vcsRemoveFiles	Delete the selected files or folders
vcsResolve	Resolve conflicts in the selected files or folders
vcsRevert	Revert selected changes
vcsShowHistory	View history of previous commits
vcsViewOnGitHub	View this file on Github
versionControlHelp	Help on using version control with RStudio
versionControlOptions	Configure version control options
versionControlProjectSetup	Setup version control for the current project
versionControlShowRsaKey	Show RSA public key
viewAllPrefs	View All Prefs
viewerBack	Go back
viewerClear	Remove current viewer item
viewerClearAll	Clear all viewer items
viewerCopyToClipboard	Copy to the system clipboard
viewerEditSource	Edit source file
viewerForward	Go forward
viewerPopout	Show in new window
viewerRefresh	Refresh viewer
viewerSaveAllAndRefresh	Save source files and refresh viewer
viewerSaveAsImage	Save as an image file
viewerSaveAsWebPage	Save as a standalone web page
viewerStop	Stop application

Id	Description
viewerZoom	View a larger version in a new window
wordCount	Count words in selection or document
zoomActualSize	Actual Size
zoomIn	Zoom In
zoomOut	Zoom Out
zoomPlot	View a larger version of the plot in a new window
